

1
2 **In the Claims**

3 Claims 30-39 remain in the application and are listed as follows:

4
5 1-29. (Cancelled)

6
7 30. (Previously Presented) A computer-accessible medium having one
8 or more instructions that are executable by one or more processors, the one or
9 more instructions causing the one or more processors to:

10 detect a color selected from a graphic user interface (GUI) color palette
11 associated with an authoring environment;

12 normalize component values of the selected color in accordance with a
13 number of bits-per-channel associated with the authoring environment;

14 convert the normalized component values to corresponding component
15 values in a standardized reference color coordinate system; and

16
17 convert the component values in the standardized reference color
18 coordinate system to corresponding component values in a receiver color
19 coordinate system.

20
21 31. (Previously Presented) A computer-accessible medium according to
22 Claim 30, wherein the GUI color palette depicts a plane of a multi-dimensional
23 color space predicated upon a dominant color selection, such that for each color
24 depicted in the GUI color palette, a component value associated with the dominant
25

1 color is static and each dimension represents an available range of another color
2 component.

3
4 32. (Previously Presented) A computer-accessible medium according to
5 Claim 30, wherein the GUI color palette depicts a rotatable 3-D rendering of an
6 X-dimensional ($X \geq 6$) color space predicated upon a dominant color selection,
7 such that for each color depicted in the GUI color palette, a component value
8 associated with the dominant color is static and each dimension represents an
9 available range of another color component.
10

11
12 33. (Original) A computer-accessible medium according to Claim 30,
13 wherein to normalize the component values of the detected color is to
14 gamma-correct the component values.
15

16
17 34. (Original) A computer-accessible medium according to Claim 30,
18 wherein to convert the component values in the standardized reference color
19 coordinate system to corresponding component values in the receiver color
20 coordinate system further is to gamma-correct the converted component values in
21 the standardized reference color coordinate system.
22

23
24 35. (Original) A computer-accessible medium according to Claim 30,
25 wherein the one or more instructions causing the one or more processors to

1 convert the component values in the standardized reference color coordinate
2 system further causes the one or more processors to calculate a minimum average
3 component value if one of the converted component values exceed a range of
4 [0,1].
5

6 36. (Original) A computer-accessible medium according to Claim 30,
7 wherein the one or more instructions causing the one or more processors to
8 convert the component values in the standardized reference color coordinate
9 system further causes the one or more processors to default to a next-closest color
10 component value match if one of the converted component values exceed a range
11 of [0,1].
12

13
14 37. (Original) A computer-accessible medium according to Claim 36,
15 wherein the next-closest color component value match is determined in
16 accordance with a mathematical projection.
17

18
19 38. (Original) A computer-accessible medium according to Claim 30,
20 further comprising one or more instructions causing the one or more processors to
21 indicate that the detected color is invalid and request another color be selected
22 from the GUI color palette if one of the converted component values exceed a
23 range of [0,1].
24
25

1 39. (Original) A computer-accessible medium according to Claim 30,
2 wherein the standardized reference color coordinate system is a CIE XYZ system.
3

4 40-54. (Cancelled)
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25